

# Spring-loaded test probe

## GKS-113 215 100 A 1502 MC


Item GKS-113-0940




**ingun**<sup>®</sup>

Partner for Future Technology

- Screw-in test probes for applications with possible vibrations or unwanted side and axial forces (migration of the test probe out of the receptacle is reliably prevented)
- The screw-in test probe is securely installed in the KS using a torque screwdriver and bit tool. The required screw-in torque is applied via a square post on the receptacle.
- Stainless steel versions for temperatures from -100 °C up to +200 °C available



1:1



### General data

|                                 |                                 |
|---------------------------------|---------------------------------|
| Product group:                  | Screw-in test probe             |
| Sub-product group:              | Screw-in test probe             |
| Series:                         | GKS-113 M screw-in              |
| Grid:                           | 4 mm [157 mil]                  |
| Contacting from:                | Pad                             |
| Magnetic:                       | Yes                             |
| Installation type:              | Screw-in                        |
| Quick-exchange system:          | Yes                             |
| Adjustable installation height: | No                              |
| Non-rotating:                   | No                              |
| Screw-in torque:                | 10 - 20 cNm [885 - 1.77 lbf-in] |
| Compatible receptacle(s):       | KS-113 M                        |
| Min. temperature:               | - 100 °C [- 212 °F]             |
| Max. temperature:               | + 200 °C [+ 392 °F]             |
| RoHS-compliant:                 | RoHS-3;6c                       |

### Electrical data

|                                        |           |
|----------------------------------------|-----------|
| Current load capacity / rated current: | 5 A       |
| Typical resistance (Ri):               | <100 mOhm |

### Mechanical data

|                                 |                   |
|---------------------------------|-------------------|
| Total length:                   | 30.8 mm [1.21 in] |
| Barrel diameter:                | 2.65 mm [.104 in] |
| Maximum stroke:                 | 5.3 mm [.208 in]  |
| Spring pre-load:                | 0.39 N [1.40 ozf] |
| Collar height:                  | 02                |
| Spring force at working stroke: | 1.5 N [5.39 ozf]  |
| Recommended working stroke:     | 4 mm [.157 in]    |

### Tip style data

|                     |                                       |
|---------------------|---------------------------------------|
| Tip style:          | 15 22° high-carbon tip, self-cleaning |
| Tip diameter:       | 1 mm [0.039 in]                       |
| Tip style surface:  | A gold                                |
| Tip style material: | 2 steel                               |

SCREW-IN TEST PROBE

# Spring-loaded test probe


## GKS-113 215 100 A 1502 MC

Item GKS-113-0940



**ingun**<sup>®</sup>

Partner for Future Technology



### INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162  
78467, Constance, Germany  
Phone +49 7531 8105-0  
Customer hotline +49 7531 8105-888  
Fax +49 7531 8105-65  
info@ingun.com



Prices and delivery times on request.  
Technical changes reserved. 03/24\_GB

Learn more about  
Screw-in test probe



SCREW-IN TEST PROBE

ingun.com