## Spring-loaded test probe


### GKS-967 215 130 A 2001 M

Item GKS-967-0087







- Short-stroke probes ensure a reliable signal and power supply, as well as a quick exchange of assemblies in case of maintenance
- For the construction of easily separable electronic interfaces, such as in charging trays for electronic devices
- Compensation of possible height and component tolerances
- Secure hold in the receptacle due to threaded connection
- Stainless steel versions for temperatures from -100 °C up to +200 °C available









#### **General data**

Product group: Assorted test probes Sub-product group: Short stroke GKS / charge and transfer GKS Series: GKS-967 M screw-in Grid: 4 mm [157 mil] Pad Contacting from: Magnetic: Yes Installation type: Screw-in Quick-exchange system: Yes Adjustable installation height: Non-rotating: Screw-in torque: 3 - 5 cNm [.265 - .442 lbf·in] Compatible receptacle(s): KS-967 M Min. temperature: - 40 °C [- 104 °F] + 80 °C [+ 176 °F] Max. temperature: RoHS-compliant: RoHS-3;6a;6c

#### **Electrical data**

Current load capacity / rated current: 5 A Typical resistance (Ri): <10 mOhm

#### **Mechanical data**

Total length: 6.8 mm [.267 in] Barrel diameter: 2.5 mm [.098 in] Maximum stroke: 1.2 mm [.047 in] Spring pre-load: 0.57 N [2.05 ozf] Collar height: 01 Spring force at working stroke: 2 N [7.19 ozf] Recommended working stroke: 1 mm [.039 in]

#### Tip style data


Tip style: 15 22° high-carbon tip, self-cleaning Tip diameter: 1.3 mm [.051 in] Tip style surface: A gold Tip style material: 2 steel

# Partner for Future Technology

## Spring-loaded test probe GKS-967 215 130 A 2001 M

Item GKS-967-0087





#### **INGUN** Prüfmittelbau GmbH

Max-Stromeyer-Straße 162 78467, Constance, Germany Phone +49 7531 8105-0 Customer hotline +49 7531 8105-888 Fax +49 7531 8105-65 info@ingun.com







Learn more about Screw-in test probe

