

**GWDR M40-NP****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Similar to illustration**

In addition to cable glands for a wide range of applications, the product portfolio is rounded off by plugs, pressure compensation elements, adaptors and the corresponding accessories such as locknuts, sealing rings, flat washers and earthing rings.

**General ordering data**

|            |                                                                |
|------------|----------------------------------------------------------------|
| Version    | GWDR NP (flat gasket - neoprene), Sealing ring, M 40, Neoprene |
| Order No.  | <a href="#">1736270000</a>                                     |
| Type       | GWDR M40-NP                                                    |
| GTIN (EAN) | 4008190956066                                                  |
| Qty.       | 20 pc(s).                                                      |

**GWDR M40-NP****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Dimensions and weights**

|            |        |                 |            |
|------------|--------|-----------------|------------|
| Height     | 1.5 mm | Height (inches) | 0.059 inch |
| Net weight | 2.3 g  |                 |            |

**Temperatures**

|                       |                  |
|-----------------------|------------------|
| Operating temperature | -40 °C... 100 °C |
|-----------------------|------------------|

**General information**

|                                   |          |                                   |        |
|-----------------------------------|----------|-----------------------------------|--------|
| Cable glands                      | M 40     | Diameter of sealing ring          | 52 mm  |
| External thread                   | M 40     | Halogen                           | Yes    |
| Inside diameter D2                | 40 mm    | Internal thread                   | M 40   |
| Material                          | Neoprene | Number of wires                   | 1      |
| O.D.                              | 52 mm    | Operating temperature range, max. | 100 °C |
| Operating temperature range, min. | -40 °C   | Pitch of thread                   | 1.5 mm |
| Sealing                           | Neoprene | Silicone                          | No     |
| Thickness                         | 1.5 mm   |                                   |        |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001181    | ETIM 7.0    | EC001181    |
| ETIM 8.0    | EC001181    | ETIM 9.0    | EC001181    |
| ECLASS 9.0  | 27-43-03-19 | ECLASS 9.1  | 27-14-44-90 |
| ECLASS 10.0 | 27-43-03-19 | ECLASS 11.0 | 27-43-03-19 |
| ECLASS 12.0 | 27-43-03-19 | ECLASS 13.0 | 27-43-03-19 |

**Environmental Product Compliance**

|            |   |
|------------|---|
| REACH SVHC | / |
|------------|---|

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                  |                                          |
|------------------|------------------------------------------|
| Engineering Data | <a href="#">CAD data – STEP</a>          |
| Catalogues       | <a href="#">Catalogues in PDF-format</a> |
| Brochures        |                                          |

## GWDR M40-NP

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

