USB configurable monolithic tower light, Harmony XVGU, multi color programmable lights 60mm, steady/flashing LED buzzer

XVGU3SWV

Main

Range of product	Harmony XVGU
Product or component type	USB configurable monolithic tower light
Beacon or indicator bank unit type	3 illuminated units
Sound signalling	Buzzer
Mounting diameter	60 mm
Component name	XVGU
Light source	LED steady or flashing multi-colour
Indicator bank base type	Base with integrated buzzer
Noise level	82 dB (2 tone buzzer) at 1 m

Complementary

Material	PC: globe
Device mounting	Direct mounting
Light block color	Clear/clear
[Us] rated supply voltage	5 V DC
Connector type	USB type A female
Current consumption	400 mA
Sound frequency	2700 Hz 3800 Hz
Power consumption in W	2 W
Flashing frequency	2 Hz with flashing LED unit 1 Hz with flashing LED unit
Product compatibility	Vijeo Designer 4.6 indoor use only HMIGTO XBTGT XBTGK XBTGKC1. XBTGC2. XBTGH
Net weight	0.3 kg

Environment

Standards EN 61000-6-2 EN 61000-6-4

Product certifications	GOST cUL CE RCM UL 508
Ambient air temperature for storage	-3570 °C
Ambient air temperature for operation	055 °C
Electrical shock protection class	Class I
IP degree of protection	IP54
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.9 cm
Package 1 Width	7.9 cm
Package 1 Length	31.1 cm
Package 1 Weight	350.0 g
Unit Type of Package 2	S04
Number of Units in Package 2	21
Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	8.6 kg
Unit Type of Package 3	P06
Number of Units in Package 3	84
Package 3 Height	80 cm
Package 3 Width	80 cm
Package 3 Length	60 cm
Package 3 Weight	42.908 kg
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Contractual warranty

Warranty

18 months


Product data sheet

XVGU3SWV

Dimensions Drawings

Dimensions

Direct Base Mounting




Product data sheet

XVGU3SWV

Mounting and Clearance

Mounting on Horizontal Support for Direct Base Mounting




- Cable outlet
- (1) (2) (3) (4) Buzzer opening position Waterproof rubber seal Hexagon nut with flange

Product data sheet

XVGU3SWV

Mounting and Clearance

Mounting Orientation



Choose a flat surface with enough strength and with little vibration for installation. Mount this product according to the figure to maintain IP characteristics of the figure to maintain IP characteristics. NO

- (1) (2)

Recommended replacement(s)