

Radio-frequency probe

HFS-856 303 051 A 5042 SMP-H

Item HFS-856-0023



GO TO PRODUCT

ingun®


Partner for Future Technology

- For contacting plug connectors, micro-connectors micro-switches
- Up to 12 GHz
- Cable interface SMA
- Installation via flange mounting



UTILITY
MODEL

PATENT
PENDING

5G
READY



1:1



Radio-frequency probe

HFS-856 303 051 A 5042 SMP-H

Item HFS-856-0023



GO TO PRODUCT

ingun[®]

Partner for Future Technology

General data

Product group:	HFS radio-frequency test probes
Series:	HFS-856
Sub-series:	HFS-856
Grid:	10 mm [393 mil]
DUT / contact:	SMP
Installation type:	Flange
DUT interface gender :	M signal conductor male / pin
Floating mount:	Yes
Non-rotating:	No
Continuous plunger:	Yes
Interface of compatible assembly:	SMA 50 Ohm
Compatible assembly interface gender :	M signal conductor male / pin
Recommended torque at interface:	45 cNm [3.98 lbf·in]
Min. temperature:	- 40 °C [- 104 °F]
Max. temperature:	+ 80 °C [+ 176 °F]
RoHS-compliant:	RoHS-3;6c

Outer conductor data

Outer conductor tip style:	42 centring for inner side of plug connector
Outer conductor tip style diameter:	3.4 mm [.133 in]
Spring force of entire outer conductor at working stroke:	4 N [14.3 ozf]
Outer conductor working stroke:	4.2 mm [.165 in]
Outer conductor maximum stroke:	5.2 mm [.204 in]
Exchangeable outer conductor:	No
Outer conductor max. current load capacity:	3 A

Inner conductor data

Inner conductor tip style:	03 inverse cone
Inner conductor tip style diameter:	0.51 mm [.020 in]
Inner conductor tip style material:	3 CuBe
Inner conductor tip style surface:	A gold
Number of inner conductors:	1
Exchangeable inner conductor:	No
Inner conductor working stroke:	1 mm [.039 in]
Spring force of each inner conductor at working stroke:	1 N [3.59 ozf]
Inner conductor maximum stroke:	2 mm [.078 in]
Inner conductor max. current load capacity:	2 A

Electrical data

Frequency range up to:	6 GHz
Impedance:	50 Ohm

Mechanical data

Total spring force at working stroke:	5 N [17.9 ozf]
Total length:	37.8 mm [1.48 in]
Barrel diameter:	5 mm [.196 in]
Installation height without receptacle:	24 mm [.944 in]

INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 04/24_GB

Learn more about
Radio-frequency test probes



ingun.com