

HE	XX Number of contacts	X Pitch	0	X Color	X Lever	X	X	X	X	X
	End Stackable 01 1 contacts 02 2 contacts 03 3 contacts 12 12 contacts (pitch 2.5&2.54) 08 8 contacts (pitch 5.0&5.08)	4 2.5/.098" 5 2.54/.10" 0 5.0/.197" 2 5.08/.20"	0 Black 3 Orange(RAL 2011/P) (pitch 2.5/2.54) 4 Orange(RAL 2011/P) (pitch 5.0/5.08) 5 Green(RAL 6018/T) 6 Blue(RAL 5015/A) 8 Grey(RAL 7004/P)	0 With lever 1 Without lever	0000 Standard Any special item by customer request, please contact sales department.	G ROHS compliant (lead<4%) In copper alloy H ROHS compliant (lead<1000ppm) In copper alloy				

HF	XX Number of contacts	X Pitch	0	X Color	X Body type	X	X	X	X	X
	01 1 contacts 02 2 contacts 03 3 contacts 24 24 contacts 12 12 contacts (pitch 10.0)	7 5.0/.197" 8 10.0/.394" (only low profile type)	High profile body 8 Grey(RAL 7004/P) 9 Orange(RAL 2011/P) Low profile body 0 Black 5 Green 1 Natural color 6 Blue 2 Red 8 Grey 3 Orange 9 White 4 Yellow C Multiple colors	1 High profile body (Solid block) 2 Low profile body (End stackable)	0000 Standard Any special item by customer request, please contact sales department.	G ROHS compliant (lead<4%) In copper alloy H ROHS compliant (lead<1000ppm) In copper alloy				

HG	XX Number of contacts	X Pitch	0	X Color	0	X	X	X	X	X
	End Stackable 01 1 contacts 02 2 contacts 03 3 contacts 24 24 contacts (pitch 5.0&5.08) 16 16 contacts (pitch 7.5&7.62) 12 12 contacts (pitch 10.0&10.16)	0 5.0/.197" 1 10.0/.394" 2 7.5/.295" 3 5.08/.20" 4 10.16/.40" 5 7.62/.30" 6 12.7/.50"	0 Black 2 Red (RAL 3001/D) 5 Green (RAL 6018/T) 8 Grey (RAL 7004/P) C Multiple colors	0000 Standard Any special item by customer request, please contact sales department.	G ROHS compliant (lead<4%) In copper alloy H ROHS compliant (lead<1000ppm) In copper alloy					

HH	XX Number of contacts	X Pitch	0	X Color	0	X	X	X	X	X
	End Stackable 01 1 contacts 02 2 contacts 03 3 contacts 24 24 contacts	0 5.00/.197"	0 Black 2 Red (RAL 3001/D) 5 Green (RAL 6018/T) 8 Grey (RAL 7004/P) C Multiple colors	0000 Standard Any special item by customer request, please contact sales department.	G ROHS compliant (lead<4%) In copper alloy H ROHS compliant (lead<1000ppm) In copper alloy					

HI	XX Number of contacts	X Pitch	X Body type	X Color	X Body type	X	X	X	X	X
	End Stackable 01 1 contacts 02 2 contacts 03 3 contacts 24 24 contacts (pitch 5.0) 16 16 contacts (pitch 7.5&7.62)	0 5.0/.197" 2 7.5/.295" 3 7.62/.30"	0 Hook+pillar 1 Holder+pillar (100% protected against mismatching)	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D)	0 W/O flange 2 With flange 3 With latch	0000 Standard Any special item by customer request, please contact sales department.	G ROHS compliant (lead<4%) In copper alloy H ROHS compliant (lead<1000ppm) In copper alloy			