Insulation

## Heat Shrinkable Tubing 3:1 in a Kit

## ShrinKit 321-A - with adhesive liner

The black tubing is mainly used for environmental sealing of splices and connectors. The transparent tubing is typically used for protection of cable markers.

## **Features and Benefits**

- · Adhesive lined heat shrink tubing
- Attractive and reusable kit ideal for assembling and identification
- Inner wall melts when heated and is forced into gaps
- Adhesive forms seal against moisture as tubing cools
- Black tubing mainly for the protection of connectors and splices
- Clear tubing ideal for protection of printed label markers
- Case can be re-used for storing nails, screws, nuts, fish hooks, etc.
- Compartment size changeable by simply moving yellow space dividers




ShrinKit 321-A.

MATERIAL	Polyolefin, cross-linked (PO-X)		
Shrink Ratio	3:1		
<b>Operating Temperature</b>	-55 °C to +110 °C		
Minimum Shrink Temperature	+110 °C		
Longitudinal change after shrinkage	+1 %/-15 % max.		
Dielectric Strength	15 kV/mm according to IEC 60684 P2		
Flammability	self-extinguishing (except for transparent)		
Insulation Class	A (VDE 0530)		
Specifications	SAE - AMS - DTL-23053/4 Class 3 (except clear)		



One Step to the Web!





Heat Shrinkable Tubing 3:1 with adhesive

D -	110	- /
KO	H	

сомр.	Supplied Ø D min.	Recov. Ø d max.	Length (L)	Wall (WT)	Colour	Content (pcs.)	Article-No.
1	24.0	8.0	200.0	2.50	Black (BK)	5	
2	12.0	4.0	65.0	1.70	Transparent (CL)	15	
3	6.0	2.0	50.0	1.10	Black (BK)	20	
	6.0	2.0	50.0	1.10	Transparent (CL)	20	
4	12.0	4.0	65.0	1.70	Black (BK)	15	380-03003
5	3.0	1.0	50.0	1.00	Black (BK)	50	
	3.0	1.0	50.0	1.00	Transparent (CL)	50	
6	6.0	2.0	35.0	1.10	Black (BK)	30	
6	6.0	2.0	35.0	1.10	Transparent (CL)	30	
7	24.0	8.0	200.0	2.50	Transparent (CL)	5	
8	12.0	4.0	100.0	1.70	Black (BK)	15	
9	12.0	4.0	100.0	1.70	Black (BK)	15	
10	12.0	4.0	100.0	1.70	Transparent (CL)	15	
44	3.0	1.0	40.0	1.00	Black (BK)	50	
11	3.0	1.0	40.0	1.00	Transparent (CL)	50	]

All dimensions in mm. Subject to technical changes.



For product specific approvals and specifications please refer to the Appendix.

