


## Inductive sensor

IFK3007-ANKG/2M/PUR



1 LED yellow



## Product characteristics

|                    |                  |
|--------------------|------------------|
| Electrical design  | NPN              |
| Output function    | normally open    |
| Sensing range [mm] | 7                |
| Housing            | threaded type    |
| Dimensions [mm]    | M12 x 1 / L = 60 |

## Application

|                 |                                                                                                                     |
|-----------------|---------------------------------------------------------------------------------------------------------------------|
| Special feature | Increased sensing range                                                                                             |
| Application     | Suitable for industrial, mobile, cooling and lubricating applications; Industrial applications / factory automation |

## Electrical data

|                             |            |
|-----------------------------|------------|
| Operating voltage [V]       | 10...30 DC |
| Current consumption [mA]    | < 10       |
| Protection class            | III        |
| Reverse polarity protection | yes        |

## Outputs

|                                                      |               |
|------------------------------------------------------|---------------|
| Electrical design                                    | NPN           |
| Output function                                      | normally open |
| Max. voltage drop switching output DC [V]            | 2.5           |
| Permanent current rating of switching output DC [mA] | 100           |
| Switching frequency DC [Hz]                          | 700           |
| Short-circuit protection                             | yes           |
| Overload protection                                  | yes           |

## Detection zone

|                               |               |
|-------------------------------|---------------|
| Sensing range [mm]            | 7             |
| Real sensing range $S_r$ [mm] | $7 \pm 10 \%$ |
| Operating distance [mm]       | 0...5.67      |
| Increased sensing range       | yes           |

## Accuracy / deviations

|                          |                                                                             |
|--------------------------|-----------------------------------------------------------------------------|
| Correction factor        | steel: 1 / stainless steel: 0.7 / brass: 0.5 / aluminium: 0.4 / copper: 0.3 |
| Hysteresis [% of $S_r$ ] | 3...15                                                                      |



## Inductive sensor

IFK3007-ANKG/2M/PUR

|                               |           |                                                                                                            |                                                                                  |
|-------------------------------|-----------|------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------|
| Switch point drift            | [% of Sr] | -10...10                                                                                                   |                                                                                  |
| Operating conditions          |           |                                                                                                            |                                                                                  |
| Ambient temperature           | [°C]      | -40...85                                                                                                   |                                                                                  |
| Protection                    |           | IP 65; IP 66; IP 67; IP 68; IP 69K                                                                         |                                                                                  |
| Tests / approvals             |           |                                                                                                            |                                                                                  |
| EMC                           |           | EN 61000-4-2 ESD                                                                                           | 4 kV CD / 8 kV AD                                                                |
|                               |           | EN 61000-4-3 HF radiated                                                                                   | 10 V/m                                                                           |
|                               |           | EN 61000-4-4 Burst                                                                                         | 2 kV                                                                             |
|                               |           | EN 61000-4-6 HF conducted                                                                                  | 10 V                                                                             |
|                               |           | EN 55011                                                                                                   | class B                                                                          |
| Vibration resistance          |           | EN 60068-2-6 Fc                                                                                            | 20 g (10...3000 Hz) / 50 sweep cycles, 1 octave per minute, in 3 axes            |
| Shock resistance              |           | EN 60068-2-27 Ea                                                                                           | 100 g 11 ms half-sine; 3 shocks each in every direction of the 3 coordinate axes |
| Continuous shock resistance   |           | EN 60068-2-27                                                                                              | 40 g 6 ms; 4000 shocks each in every direction of the 3 coordinate axes          |
| Fast temperature change       |           | EN 60068-2-14 Na                                                                                           | TA = -40 °C; TB = 85 °C; t1 = 30 min; t2 = < 10 s; 50 cycles                     |
| Salt spray test               |           | EN 60068-2-52 Kb                                                                                           | severity level 5 (4 test cycles)                                                 |
| MTTF                          | [years]   | 837                                                                                                        |                                                                                  |
| Embedded software included    |           | yes                                                                                                        |                                                                                  |
| UL approval                   |           | Ta                                                                                                         | -25...75 °C                                                                      |
|                               |           | Enclosure type                                                                                             | Type 1                                                                           |
|                               |           | power supply                                                                                               | Limited Voltage/Current                                                          |
|                               |           | UL Approval no.                                                                                            | A002                                                                             |
|                               |           | File number UL                                                                                             | E174191                                                                          |
| Mechanical data               |           |                                                                                                            |                                                                                  |
| Weight                        | [g]       | 76.9                                                                                                       |                                                                                  |
| Housing                       |           | threaded type                                                                                              |                                                                                  |
| Mounting                      |           | non-flush mountable                                                                                        |                                                                                  |
| Dimensions                    | [mm]      | M12 x 1 / L = 60                                                                                           |                                                                                  |
| Thread designation            |           | M12 x 1                                                                                                    |                                                                                  |
| Materials                     |           | brass white bronze coated; sensing face: PBT orange; LED window: PEI; lock nuts: brass white bronze coated |                                                                                  |
| Displays / operating elements |           |                                                                                                            |                                                                                  |
| Display                       |           | switching status                                                                                           | 1 x LED, yellow                                                                  |
| Accessories                   |           |                                                                                                            |                                                                                  |
| Items supplied                |           | lock nuts: 2                                                                                               |                                                                                  |
| Remarks                       |           |                                                                                                            |                                                                                  |
| Pack quantity                 |           | 1 pcs.                                                                                                     |                                                                                  |

# IFS255




## Inductive sensor

IFK3007-ANKG/2M/PUR

### Electrical connection

Cable: 2 m, PUR, Ø 4 mm; burning behaviour to ECE R118 rev. 2; 3 x 0.34 mm<sup>2</sup>

### Connection



|      |                |
|------|----------------|
| BK = | Core colours : |
| BN = | black          |
| BU = | brown          |
|      | blue           |