


**IC080173****INDUCTIVE SENSORS • FULL-METAL HOUSING**

sensor inductive, all-steel, M8x1 46long, Quasi-flat, Sn: 2, 10-30V  
DC, PNP NO, Connector M8 3pin, IP67, V4A, 20bar

**MECHANICAL FEATURES**

Active area material of sensor	Stainless steel 1.4404
Alignment of cable entry	Axial
Ambient temperature	-25 °C ... 75 °C
Cable infeed	Axial
Degree of protection (IP)	IP67
Design	Cylinder, screw-thread
Housing material	Stainless steel 1.4404
Max. operating pressure	20 bar
Mechanical mounting condition for sensor	Quasi-flat
Pressure-proof	+
Sensor length	46 mm
Thread length	34 mm
Thread pitch	1 mm
Thread size, metric	8

**ELECTRICAL FEATURES**

Cascadable	-
Correction factor (copper)	0.35
Correction factor (stainl. steel)	0.55
Hysteresis	20 %
No-load current	20 mA
Norm measuring plate	9x9x1
Number of pins	3
Rated switching current	200 mA
Reverse polarity protection	+
Short-circuit protection	+
Suitable for safety functions	-
Supply voltage	10 V ... 30 V
Switching distance	2 mm
Switching frequency	150 Hz
Type of electrical connection	Connector M8
Type of switching function	Normally open contact
Type of switching output	PNP

## ELECTRICAL FEATURES

Voltage drop	2 V
Voltage type	DC
With LED display	+
With monitoring function of downstream devices	-

## OTHER FEATURES

Feeding technology	+
Harsh environmental conditions	+
Hygienic and wet area	+
Metallic sensor surface	+
Oil and cooling lubricants	+


## Other


Packaging dimensions	100mm x 17.0mm x 120mm
Shipping weight	0.02kg
Tariff code	85365019

## Classification

ipf product group	204
eClass 8.0	27270101
eClass 9.0	27270101
eClass 9.1	27270101
ETIM-5.0	EC002714
ETIM-6.0	EC002714
ETIM-7.0	EC002714

## Connection



**Dimensional drawing****Installation**

Mounting / installation may only be carried out by a qualified electrician!

**Disposal****Safety warnings**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.