

#### 10080276

## **INDUCTIVE SENSORS • FULL-METAL HOUSING**

sensor inductive, all-steel, M8x1 60long, Non-flush, Sn: 6, 10-30V DC, 85°C, PNP NC, Connector M8 3pin, IP67, Stainless steel 1.4305, 100bar, factor 1



# **MECHANICAL FEATURES**

| Active area material of sensor           | Stainless steel 1.4305 |
|--|------------------------|
| Alignment of cable entry                 | Axial                  |
| Ambient temperature                      | -25 °C 85 °C           |
| Cable infeed                             | Axial                  |
| Degree of protection (IP)                | IP67                   |
| Design                                   | Cylinder, screw-thread |
| High-pressure-proof sensors              | +                      |
| Housing material                         | Stainless steel 1.4305 |
| Material independent sensors (factor 1)  | +                      |
| Material thickness                       | 0.25 mm                |
| Max. operating pressure                  | 100 bar                |
| Mechanical mounting condition for sensor | Non-flush              |
| Pressure resistance                      | 100 bar                |
| Pressure-proof                           | +                      |
| Sensor length                            | 60 mm                  |
| Thread length                            | 41.5 mm                |
| Thread pitch                             | 1 mm                   |
| Thread size, metric                      | 8                      |

## **ELECTRICAL FEATURES**

| Cascadable                                   |        |
|--|--------|
| Correction factor (aluminum)                 | 1      |
| Correction factor (brass)                    | 1.4    |
| Correction factor (copper)                   | 0.85   |
| Correction factor (St37)                     | 1      |
| Correction factor (stainless steel V2A: 1mm) | 0.3    |
| Correction factor (stainless steel V2A: 2mm) | 0.9    |
| Hysteresis                                   | 20 %   |
| Max. line length                             | 300 m  |
| No-load current                              | 10 mA  |
| Norm measuring plate                         | 9x9x1  |
| Number of pins                               | 3      |
| Rated switching current                      | 200 mA |



## **ELECTRICAL FEATURES**

| Readiness delay                                | 10 ms                   |
|--|-------------------------|
| Relative repeat accuracy                       | 5 %                     |
| Residual ripple                                | 20 %                    |
| Reverse polarity protection                    | +                       |
| Short-circuit protection                       | +                       |
| Suitable for safety functions                  | -                       |
| Supply voltage                                 | 10 V 30 V               |
| Switching distance                             | 6 mm                    |
| Switching frequency                            | 700 Hz                  |
| Type of electrical connection                  | Connector M8            |
| Type of switching function                     | Normally closed contact |
| Type of switching output                       | PNP                     |
| Voltage drop                                   | 2 V                     |
| Voltage type                                   | DC                      |
| With LED display                               | +                       |
| With monitoring function of downstream devices | -                       |
|  |                         |

#### **OTHER FEATURES**

| Harsh environmental conditions | + |
|--------------------------------|---|
| Metallic sensor surface        | + |
| Oil and cooling lubricants     | + |


# Other

| Packaging dimensions | 100mm x 12.0mm x 120mm |
|----------------------|------------------------|
| Shipping weight      | 0.02kg                 |
| Tariff code          | 85365019               |

## Classification


| ipf product group | 205      |
|-------------------|----------|
| eClass 8.0        | 27270101 |
| eClass 9.0        | 27270101 |
| eClass 9.1        | 27270101 |
| ETIM-5.0          | EC002714 |
| ETIM-6.0          | EC002714 |
| ETIM-7.0          | EC002714 |

## Connection





# **Dimensional drawing**



#### Installation



Mounting / installation may only be carried out by a qualified electrician!

# Disposal



## Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information. Never use these devices in applications where the safety of a person depends on their functionality.

LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.