


**KB32A112**
**CAPACITIVE SENSORS • NORM SWITCHING DISTANCE**

sensor capacitive, M32x1.5 70long, Flush, Sn: 2-25, 10-35V DC, PNP/NPN Programmable/configurable, Cable 2m PVC, IP67, Brass, LED, Manual adjustment


**MECHANICAL FEATURES**

Active area material of sensor	Polytetrafluorethylene (PTFE)
Ambient temperature	-25 °C ... 70 °C
Cable length	2 m
Degree of protection (IP)	IP67
Design	Cylinder, screw-thread
Housing material	Brass
Material of cable sheath	PVC
Mechanical mounting condition for sensor	Flush
Number of cores	3
Pressure-proof	-
Sensor length	70 mm
Thread pitch	1.5 mm
Thread size, metric	32
Wire cross section	0.75 mm <sup>2</sup>

**ELECTRICAL FEATURES**

Cascadable	-
No-load current	15 mA
Rated switching current	400 mA
Residual ripple	10 %
Reverse polarity protection	+
Setting procedure	Manual adjustment
Short-circuit protection	+
Suitable for safety functions	-
Supply voltage	10 V ... 35 V
Switching distance	20 mm
Switching distance	2 mm ... 25 mm
Switching frequency	50 Hz
Type of electrical connection	Cable
Type of switching function	Programmable/configurable
Type of switching output	PNP/NPN
Voltage drop	2 V
Voltage type	DC

## ELECTRICAL FEATURES

With LED display	+
With monitoring function of downstream devices	-

## OTHER FEATURES

Level detection	+
Level detection of synthetic granules for injection molding machines	+


## Other

Packaging dimensions	124.0mm x 35.0mm x 149.0mm
Shipping weight	0.35kg
Tariff code	85365019

## Classification

ipf product group	700
eClass 8.0	27270102
eClass 9.0	27270102
eClass 9.1	27270102
ETIM-5.0	EC002715
ETIM-6.0	EC002715
ETIM-7.0	EC002715

## Connection



## Dimensional drawing

## Installation



Mounting / installation may only be carried out by a qualified electrician!

## Disposal



## Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.