


OG020373
OPTICAL SENSORS • FORKED LIGHT BARRIERS

sensor optical, fork, 34x14x60mm, fork width 2mm, 10-35V DC, 1x PNP NC/NO, Connector M8 3pin, IP67, Zinc die-cast+Plastic, Infrared light, 3kHz pulsed, Teach-In


MECHANICAL FEATURES

Ambient temperature	-10 °C ... 60 °C
Degree of protection (IP)	IP67
Design	Cuboid
Diameter detection	-
Fork depth	40 mm
Fork light barrier design	Furcate
Fork width	2 mm
Housing material	Zinc die-cast
Installation bracket	-
Material of optical surface	Plastic
Sensor height	34.5 mm
Sensor length	14 mm
Sensor width	60 mm

ELECTRICAL FEATURES

Analog output 0 V ... 10 V	-
Analog output 4 mA ... 20 mA	-
Connection to amplifier	-
Decay time	0.17 ms
Dynamic switching output	-
Equipment protection class	Protection class 3
Hysteresis	0.1 mm
No-load current	35 mA
Number of pins	3
Number of switching outputs	1
Operating voltage	10 V ... 35 V
Rated switching current	200 mA
Relative repeat accuracy	0.03 mm
Repeatability +/-	30 µm
Response time	0.17 ms
Reverse polarity protection	+
Scanning function	Light-/dark-on mode
Setting procedure	Teach-In

ELECTRICAL FEATURES

Short-circuit protection	+
Switching frequency	3000 Hz
Type of electrical connection	Connector M8
Type of switching function	Normally closed contact/normally open contact
Type of switching output	PNP
Type of the forked light barrier	Standard
Voltage drop	2 V
Voltage type	DC
With communication interface, analog	-
With communication interface, RS-232	-
With other analog output	-
With time function	-

OPTICAL FEATURES

Min. object size	0.5 mm
Resolution	500 µm
Light beam form	Point
Pulsed light source	+


Other

Packaging dimensions	77.0mm x 25.0mm x 123.0mm
Shipping weight	0.1kg
Tariff code	85365019

Classification

ipf product group	110
eClass 8.0	27270909
eClass 9.0	27270909
eClass 9.1	27270909
ETIM-5.0	EC002720
ETIM-6.0	EC002720
ETIM-7.0	EC002720

Connection

Dimensional drawing**Installation**

Mounting / installation may only be carried out by a qualified electrician!

Disposal**Safety warnings**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.