

OT450528
OPTICAL SENSORS • DIFFUSE REFLECTION SENSORS WITH BACKGROUND SUPPRESSION

sensor optical, diffuse-reflection sensor, 57x38x20mm, Sn: 30-400, 10-30V DC, 1x PNP/NPN Push-pull, IO-Link, Connector M12 4pin, IP67, V4A+PMMA, 1kHz, Background suppression, Polarity free red light, Point, Teach-In


MECHANICAL FEATURES

Ambient temperature	-25 °C ... 60 °C
Degree of protection (IP)	IP67
Design	Cuboid
Housing material	Stainless steel 1.4404
Material of optical surface	PMMA
Reflector included in the scope of delivery	-
Sensor height	57 mm
Sensor length	37.7 mm
Sensor width	20 mm
Volume	Medium

ELECTRICAL FEATURES

Adjustment range	30 mm ... 600 mm
Analog output 0 mA ... 20 mA	-
Analog output 0 V ... 10 V	-
Analog output -10 V ... +10 V	-
Analog output 4 mA ... 20 mA	-
Decay time	0.49 ms
Interference suppression	+
IO-Link compatible	+
Max. switching distance	400 mm
Min. switching distance	30 mm
No-load current	30 mA
Number of pins	4
Number of switching outputs	1
Operating voltage	10 V ... 30 V
Rated switching current	100 mA
Rated switching distance	400 mm
Response time	0.49 ms
Reverse polarity protection	+
Scanning function	Light-/dark-on mode
Sensing range	30 mm ... 400 mm
Setting procedure	Teach-In

ELECTRICAL FEATURES

Short-circuit protection	+
Switching frequency	1000 Hz
Type of electrical connection	Connector M12
Type of switching function	Push-pull
Type of switching output	PNP/NPN
Voltage drop	3 V
Voltage type	DC
With LED display	+
With LED display (operation)	+
With LED display (signal)	+
With other analog output	-
With time function	-

OPTICAL FEATURES

Light source	Polarity free red light
Wavelength of the sensor	630 nm
Triangulation	Background suppression
Light beam form	Point
Background suppression	+
Small light beam diameter	+


Other


Packaging dimensions	77.0mm x 25.0mm x 123.0mm
Shipping weight	
Tariff code	85365019

Classification

ipf product group	100
eClass 8.0	27270904
eClass 9.0	27270904
eClass 9.1	27270904
ETIM-5.0	EC002719
ETIM-6.0	EC002719
ETIM-7.0	EC002719

Connection



Dimensional drawing**Installation**

Mounting / installation may only be carried out by a qualified electrician!

Disposal**Software**

Any software, drivers or IODD files that may be required to operate your device can be downloaded free of charge from our homepage: www.ipf-electronic.com

Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.