

OTQ30170**OPTICAL SENSORS • DIFFUSE REFLECTION SENSORS WITH INTENSITY DIFFERENTIATION**

sensor optical, diffuse-reflection sensor, 20x3,5x13mm, Sn: 2-25, 12-24V DC, 1x PNP NO (NO), Cable connector M8 3pin 0.3m PVC, IP67, Plastic PET+Plastic, 1kHz, Polarity free red light, Point

**MECHANICAL FEATURES**

Ambient temperature	-25 °C ... 55 °C
Cable length	0.3 m
Degree of protection (IP)	IP67
Design	Cuboid
Housing material	Plastic PET
Material of cable sheath	PVC
Material of optical surface	Plastic
Number of cores	3
Reflector included in the scope of delivery	-
Sensor height	20.5 mm
Sensor length	3.5 mm
Sensor width	13 mm
Shock resistance	50 g
Storage temperature	-30 °C ... 70 °C
Vibration resistance	500 Hz
Volume	Small
Wire cross section	0.1 mm ²
With interchangeable lens	-

ELECTRICAL FEATURES

Alarm output	-
Decay time	0.5 ms
Equipment protection class	Protection class 3
High repeat accuracy	-
Hysteresis	15 %
Interference suppression	-
Max. switching distance	25 mm
No-load current	20 mA
Number of pins	3
Number of switching outputs	1
Operating voltage	12 V ... 24 V
Pre-failure message	-
Rated switching current	50 mA

ELECTRICAL FEATURES

Residual ripple	10 %
Response time	0.5 ms
Reverse polarity protection	+
Scanning function	Light switching
Sensing range	2 mm ... 25 mm
Short-circuit protection	+
Suitable for safety functions	-
Switching frequency	1000 Hz
Type of electrical connection	Cable connector M8
Type of switching function	Normally open contact (NO)
Type of switching output	PNP
Voltage drop	1 V
Voltage type	DC
With communication interface, RS-232	-
With LED display	+
With monitoring function of downstream devices	-
With other analog output	-
With restart lock	-
With time function	-

OPTICAL FEATURES

Light source	Polarity free red light
Wavelength of the sensor	680 nm
Light exit	Axial
Light beam form	Point
Small light beam diameter	-
Line scanner	-

OTHER FEATURES

Feeding technology	+
For gloss queries	-
Is line scan camera	-


Other

Packaging dimensions	77.0mm x 25.0mm x 123.0mm
Shipping weight	0.04kg
Tariff code	85365019


Classification

ipf product group	100
eClass 8.0	27270903
eClass 9.0	27270903
eClass 9.1	27270903
ETIM-5.0	EC001821
ETIM-6.0	EC001821
ETIM-7.0	EC001821

Connection



Dimensional drawing



Installation



Mounting / installation may only be carried out by a qualified electrician!

Disposal



Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.