

VK50A165

CONNECTION TECHNOLOGY • CABLE SOCKETS / CONNECTORS PRE-ASSEMBLED ON ONE SIDE

, 5m, M12 Female (socket) 4pin Straight, Free conductor end, $4x0.25 mm^2,\, PVC,\, \rlap/{\phi}5 mm$



MECHANICAL FEATURES

Cable infeed of A connection	Straight
Cable length	5 m
Material of cable sheath	PVC
Number of cores	4
Perm. ambient temperature of cable, fixed cable	-25 °C 70 °C
Version	Connection cable
Wire assembly	32 x 0.1mm
Wire cross section	0.25 mm ²

ELECTRICAL FEATURES

Line diameter	5 mm
Number of pins of A connection	4
Type of A electrical connection	M12
Type of B electrical connection	Free conductor end
Type of plug-in contact, A connection	Female (socket)

OTHER FEATURES

IR-networked	_
IN-HELWOINEU	

Other


Packaging dimensions	155.0mm x 20mm x 180mm
Shipping weight	0.18kg
Tariff code	85444290

Classification

ipf product group	700
eClass 8.0	27279218
eClass 9.0	27060311
eClass 9.1	27060311
ETIM-5.0	EC001855
ETIM-6.0	EC001855
ETIM-7.0	EC001855



Connection



Dimensional drawing

Installation



Mounting / installation may only be carried out by a qualified electrician!

Disposal



Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information. Never use these devices in applications where the safety of a person depends on their functionality.

LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.