

VKA0A332
CONNECTION TECHNOLOGY • CABLE SOCKETS / CONNECTORS PRE-ASSEMBLED ON ONE SIDE

, 10m, M12 Female (socket) 4pin Angular, Free conductor end,
4x0.25mm², PVC, Ø5mm


MECHANICAL FEATURES

Cable infeed of A connection	Angular
Cable length	10 m
Material of cable sheath	PVC
Number of cores	4
Perm. ambient temperature of cable, fixed cable	-25 °C ... 70 °C
Version	Connection cable
Wire assembly	32 x 0.1mm
Wire cross section	0.25 mm ²

ELECTRICAL FEATURES

Line diameter	5 mm
Number of pins of A connection	4
Type of A electrical connection	M12
Type of B electrical connection	Free conductor end
Type of plug-in contact, A connection	Female (socket)

OTHER FEATURES


IR-networked	-
--------------	---

Other

Packaging dimensions	160mm x 30mm x 195.0mm
Shipping weight	0.35kg
Tariff code	85444290

Classification

ipf product group	700
eClass 8.0	27279218
eClass 9.0	27060311
eClass 9.1	27060311
ETIM-5.0	EC001855
ETIM-6.0	EC001855
ETIM-7.0	EC001855

Connection

- 1 brown
- 2 white
- 3 blue
- 4 black

Dimensional drawing**Installation**

Mounting / installation may only be carried out by a qualified electrician!

Disposal**Safety warnings**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.