


IS5086



Inductive sensor

IS-3003BBPKG/0,15M AS



Product characteristics		
Electrical design		PNP
Output function		normally open
Sensing range	[mm]	3
Housing		rectangular
Dimensions	[mm]	28 x 10 x 16
Electrical data		
Operating voltage	[V]	10...30 DC; ("supply class 2" to cULus)
Current consumption	[mA]	< 15
Protection class		III
Reverse polarity protection		yes
Outputs		
Electrical design		PNP
Output function		normally open
Max. voltage drop switching output DC	[V]	2.5
Permanent current rating of switching output DC	[mA]	200
Short-circuit protection		yes
Overload protection		yes
Detection zone		
Sensing range	[mm]	3
Real sensing range Sr	[mm]	3 ± 10 %
Operating distance	[mm]	0...2.4
Accuracy / deviations		
Hysteresis	[% of Sr]	1...15

IS5086



Inductive sensor

IS-3003BBPKG/0,15M AS

Switch point drift	[% of Sr]	-10...10
--------------------	-----------	----------

Operating conditions

Ambient temperature	[°C]	0...60
Protection	IP 65; IP 67; (with ifm socket duly screwed on)	

Tests / approvals

EMC	EN 60947-5-2	
MTTF	[years]	2965
UL approval	Ta	0...60 °C
	Enclosure type	Type 1
	power supply	Class 2
	File number UL	E174191

Mechanical data

Weight	[g]	14.3
Housing	rectangular	
Mounting	flush mountable	
Dimensions	[mm]	28 x 10 x 16
Materials	PBT; PC	
Tightening torque	[Nm]	< 0.5; (with washer)

Displays / operating elements

Display	switching status	1 x LED, yellow
---------	------------------	-----------------


Remarks

Pack quantity	1 pcs.
---------------	--------

Electrical connection - plug

Cable: 0.15 m, PUR

Connector: 1 x M8; coding: A





Inductive sensor

IS-3003BBPKG/0,15M AS

Connection

