


INDEX:
KABX-3PFS-L400

CONNECTION CABLE WITH MOLEX CONNECTOR



PRODUCT NAME:
TLYp cable with Molex 3PIN MX-43645-0300

CONSTRUCTION DETAILS:
TLYp type cable with $3 \times 0,35 \text{ mm}^2$ core area, black PVC insulation, class 5 copper stranded wire, one core marked with a red color with a Molex MX-43645-0300 connector and Molex MX-43030-0007 machine crimp contacts, tinned end of the cable.

APPLICATIONS:
For stationary installations in dry and damp places and for installation inside devices in medium operating conditions (e.g. in washing machines, dryers, refrigerators, and other home appliances, portable work equipment, home consumer electronics). Devices requiring cables with high flexibility where there is no risk of contact with hot parts in applications such as:

- audio systems and loudspeaker installations,
- alarm and intercom systems,
- building and home automation systems,
- control devices in electronic and industrial automation installations,
- LED lighting (LED).

TECHNICAL SPECIFICATION:

Temperature range [°C]	From -15 to 70
Maximum working voltage [V]	150
Minimum insulation strength for alternating current 50 Hz [VAC]	1000
Maximum current [A]	4
Insulation material	PVC
Core area [mm ²]	$3 \times 0,35$
External dimensions of the cable [mm]	1,6×3,4
Colors of the cores	Black/Red
Core material	Copper
Core type	Stranded wire
Cable length [mm]	400
Connector designator	MX-43645-0300
Connector type	Micro-Fit 3.0 Molex
Number of pins	3
Connector type	Female
ROHS 2015/863	Compliant
LVD 2014/35/UE	Compliant

The cable cannot be used for high-current installation outside devices.