



## KL4428 | 8-channel analog output terminal 4...20 mA

The KL4428 analog output terminal generates signals in the range between 4 to 20 mA. The power is supplied to the process level with a resolution of 12 bits and is electrically isolated. The output stage is powered by the 24 V supply. The KL4428 combines eight channels in one housing and is particularly suitable for space-saving installation in control cabinets. The use of single conductor connection technology enables the connection of multi-channel actuator technology with minimum space requirements.

The Bus Terminal has a common ground potential. The power contacts are connected through. The reference ground of the outputs is the 0 V power contact. The LEDs indicate the data exchange with the Bus Coupler.

Technical data	KL4428   KS4428
Technology	single-ended
Number of outputs	8
Power supply	24 V DC via power contacts (alternative 15 V DC with power supply terminal KL9515)
Signal current	4...20 mA
Load	< 150 $\Omega$ (short-circuit-proof)
Output error	< $\pm 0.2$ % (relative to end value)
Resolution	12 bit
Conversion time	~ 8 ms
Electrical isolation	500 V (K-bus/signal voltage)
Current consumption power contacts	typ. 60 mA + load
Current consumption K-bus	typ. 20 mA
Bit width in the process image	output: 8 x 16 bit data (8 x 8 bit control/status optional)
Special features	increased packing density
Weight	approx. 75 g
Operating/storage temperature	0...+55 °C/-25...+85 °C
Relative humidity	95 %, no condensation
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4
Protect. class/installation pos.	IP 20/variable
Pluggable wiring	for all KSxxxx Bus Terminals
Approvals	CE, UL, Ex, GL

Special terminals	
KL4428-0050	Siemens S7 format