

Home - Fischerelektronik - LA ICK PEN 16 W 12 A

fischerelektronik.de/web_fischer/en_GB/VA/LAICKPEN16W12A/datasheet.xhtml

Features

way of fixation: therm. cond. adhesive

socket:

- socket 7
- socket 370

thermal resistance: 1.2 K/W

suitable for processor type:

- AMD[®] K6-III
- IDT W2A
- Cyrix MII and similar
- MMX
- IDT C6
- Intel[®] Pentium[®]
- AMD[®] K6-2


dissipation loss: 51.1 W

operating voltage of the fan motor: 12 V

surface: black anodised

accessories: alarm exit

Technical Drawing



A: 50.8 mm

B: 50.8 mm

C: 16.51 mm

D: 26.51 mm

Fan

circuit voltage: 10.2...13.8 V DC

bearing type: double ball bearing

fan dimensions: 40x40x10 mm

cur. consumpt.: 50 mA

max. iuitial current: 130 mA

max. volume flow: 173 l/min
10.3 m³/h

max. static pressure: 2.9 mmH₂O
28.5 Pa

noise level: 24 dB(A), 1 m lateral

temperature range: -40°C... +80°C

failure rate (L₁₀): 95,000 h

MTBF: 280,000 h (20°C)

weight: 13 g

cases: plastic PBT
(UL E54695)