

# Home - Fischerelektronik - LA ICK PEN 38 W 12

---

[fischerelektronik.de/web\\_fischer/en\\_GB/VA/LAICKPEN38W12/datasheet.xhtml](http://fischerelektronik.de/web_fischer/en_GB/VA/LAICKPEN38W12/datasheet.xhtml)



Heatsinks and active heatsinks for processors>Active heatsinks for processors  
for Intel Pentium and MMX

## Features

---

way of fixation: therm. cond. adhesive

---

socket: 

- socket 7
- socket 370

---

thermal resistance: 1.1 K/W

---

suitable for processor type: 

- AMD® K6-III
- IDT W2A
- Cyrix MII and similar
- MMX
- IDT C6
- Intel® Pentium®
- AMD® K6-2

---

---

dissipation loss: 53.6 W

---


operating voltage of the fan motor: 12 V

---

surface: black anodised

## Technical Drawing

---



A: 49.5 mm

---

B: 49.5 mm

---

C: 38 mm

---

D: 48 mm

## Fan

---

---

circuit voltage:	10.2...13.8 V DC
bearing type:	ball bearing
fan dimensions:	50x50x10 mm
cur. consumpt.:	50 mA
max. iuitial current:	140 mA
max. volume flow:	238 l/min 14.3 m <sup>3</sup> /h
max. static pressure:	2.7mm H <sub>2</sub> O 26.9 Pa
noise level:	22 dB(A), 1 m lateral
temperature range:	-10°C... +70°C
failure rate (L <sub>10</sub> ):	95,000 h
MTBF:	280,000 h (20°C)
weight:	19 g
cases:	plastic PBT (UL E54695)