



Heatsinks and active heatsinks for processors>Active heatsinks for processors
for Intel Pentium and MMX


Features

way of fixation:	therm. conductive foil
socket:	• socket 7 • socket 370
thermal resistance:	2.5 K/W
suitable for processor type:	• AMD® K6-III • IDT W2A • Cyrix MII and similar • MMX • IDT C6 • Intel® Pentium® • AMD® K6-2
dissipation loss:	23.4 W
operating voltage of the fan motor:	5 V

surface:

black anodised

Technical Drawing



A: 50.8 mm

B: 50.8 mm

C: 8 mm

D: 9 mm

Fan

circuit voltage:	4.5...5.5 V DC
------------------	----------------

bearing type:	ball bearing
---------------	--------------

fan dimensions:	44x44x6.2 mm
-----------------	--------------

cur. consumpt.:	90 mA
-----------------	-------

max. iuitial current:	160 mA
-----------------------	--------

max. volume flow:	50 l/min 3 m ³ /h
-------------------	---------------------------------

max. static pressure:	2.6mm H ₂ O 25.5 Pa
-----------------------	-----------------------------------

noise level:	28 dB(A), 1 m lateral
--------------	-----------------------

temperature range:	-40°C... +80°C
--------------------	----------------

failure rate (L ₁₀):	95,000 h
----------------------------------	----------

MTBF:	280,000 h (20°C)
-------	------------------

weight:	7 g
---------	-----

cases:	plastic PBT (UL E54695)
--------	----------------------------

Fischer Elektronik GmbH & Co. KG
DEUTSCHLAND • GERMANY • ALLEMAGNE

Nottebohmstraße 28
58511 Lüdenscheid

Telefon +49 2351 435-0
Telefax +49 2351 45754

info@fischerelektronik.de
www.fischerelektronik.de