

## Data sheet Product LAM 4 100 5






Cooling aggregates>Miniature cooling aggregates  
40 x 40 mm, with axial fan

### Features

width:	40 mm
height:	40 mm
length:	100 mm
thermal resistance:	1.1 - 0.6 K/W
operating voltage of the fan motor:	<ul style="list-style-type: none"> <li>• 5 V DC</li> <li>• 12 V DC</li> <li>• 24 V DC</li> </ul>
surface:	natural colour anodised

### Technical Drawing



**Fan****ebmpapst 405, 5 V DC**

type:	ebmpapst 405
dimensions:	40x40x20 mm
tension:	5 V DC
power inout:	0.9 W
max. air volume:	10 m <sup>3</sup> /h
temperature range:	-20°C... +70°C
speed:	6,000 min <sup>-1</sup>
noise level:	18 dB(A)
weight:	27 g
failure rate (L <sub>10</sub> ):	L <sub>10</sub> < 50,000 h (40°C) L <sub>10</sub> < 20,000 h (tmax)

**ebmpapst 412 JHH, 12 V DC**

type:	ebmpapst 412 JHH
dimensions:	40x40x25 mm
tension:	12 V DC
power inout:	3.3 W
max. air volume:	24 m <sup>3</sup> /h
temperature range:	-20°C... +60°C
speed:	13,000 min <sup>-1</sup>
noise level:	46 dB(A)
weight:	50 g
failure rate (L <sub>10</sub> ):	L <sub>10</sub> < 57,500 h (40°C) L <sub>10</sub> < 35,000 h (tmax)

**ebmpapst 414 JHH, 24 V DC**

type:	ebmpapst 414 JHH
dimensions:	40x40x25 mm

tension:	<b>24 V DC</b>
power inout:	<b>3.6 W</b>
max. air volume:	<b>24 m<sup>3</sup>/h</b>
temperature range:	<b>-20°C... +60°C</b>
speed:	<b>13,000 min<sup>-1</sup></b>
noise level:	<b>46 dB(A)</b>
weight:	<b>50 g</b>
failure rate (L <sub>10</sub> ):	<b>L<sub>10</sub> &lt; 57,500 h (40°C)</b> <b>L<sub>10</sub> &lt; 35,000 h (tmax)</b>

**Fischer Elektronik GmbH & Co. KG**  
DEUTSCHLAND • GERMANY • ALLEMAGNE

Nottebohmstraße 28  
58511 Lüdenscheid

Telefon +49 2351 435-0  
Telefax +49 2351 45754

info@fischerelektronik.de  
www.fischerelektronik.de