Product data sheet Characteristics

NSYS3D6640T

Spacial S3D tspt door w/o mount.plate H600xW600xD400.IP66 IK08 RAL7035.





Main

Range	Spacial	
Product name	Spacial S3D	
Device application	Multi-purpose	
Product or component type	Compact enclosure	
Enclosure nominal height	600 Mm	
Enclosure nominal width	600 Mm	
Enclosure nominal depth	400 Mm	
Door type	Glazed	
Mounting plate description	Without mounting plate	
Type of gland plate	Standard	
Installation accessory type	Wall-mounting	
Device composition	1 body	
	1 door	
	1 lock	
	1 cable gland plate	

Complementary

Variant particularity	Gutter-shaped front rail double sheet thickness Single piece body	
Number of doors	Front face: 1 door(s)	
Door opening side	Reversible (120 °)	
Lock type	3 points lock, 3 mm double-bar	
Accessibility for operation	Front	
Removable parts	Door by hinges Cable gland plate by screws	
Material	Body: steel Door: steel and security glass	
Surface finish	Epoxy-polyester powder	
Colour	Grey (RAL 7035)	
Standards	IEC 62208	
Product certifications	CUL UL LR BV DNV GL	
Net weight	19.3 Kg	

Environment

Electromagnetic compatibility	Electromagnetic field immunity test
NEMA degree of protection	NEMA 4X/13
IK degree of protection	IK08 conforming to IEC 62262
IP degree of protection	IP66 conforming to IEC 60529

Packing Units

•		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	19.3 Kg	
Package 1 Height	61.3 Cm	
Package 1 width	61.8 Cm	
Package 1 Length	44.8 Cm	

Offer Sustainability

Green Premium product
REACh Declaration
Yes
Pro-active compliance (Product out of EU RoHS legal scope)
Yes
€Yes
China RoHS Declaration
Product Environmental Profile

Contractual warranty

Warranty	18 months

Product Life Status : Commercialised