Product data sheet Characteristics

NSYS3D6830T

Spacial S3D tspt door w/o mount.plate H600xW800xD300.IP66 IK08 RAL7035.





Main

Range	Spacial
Product name	Spacial S3D
Device application	Multi-purpose
Product or component type	Compact enclosure
Enclosure nominal height	600 Mm
Enclosure nominal width	800 Mm
Enclosure nominal depth	300 Mm
Door type	Glazed
Mounting plate description	Without mounting plate
Type of gland plate	Standard
Installation accessory type	Wall-mounting
Device composition	1 body
	2 cable gland plate
	1 door
	1 lock

Complementary

Variant particularity	Single piece body	
	Gutter-shaped front rail double sheet thickness	
Number of doors	Front face: 1 door(s)	
Door opening side	Reversible (120 °)	
Lock type	3 points lock, 3 mm double-bar	
Accessibility for operation	Front	
Removable parts	Door by hinges	
	Cable gland plate by screws	
Material	Body: steel	
	Door: steel and security glass	
Surface finish	Epoxy-polyester powder	
Colour	Grey (RAL 7035)	
Standards	IEC 62208	
Product certifications	GL	
	DNV	
	LR	
	UL	
	BV	
	cUL	
Net weight	25 Kg	

Environment

Electromagnetic compatibility	Electromagnetic field immunity test
NEMA degree of protection	NEMA 4X/13
IK degree of protection	IK08 conforming to IEC 62262
IP degree of protection	IP66 conforming to IEC 60529

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	25 Kg
Package 1 Height	61.8 Cm
Package 1 width	81.3 Cm
Package 1 Length	34.8 Cm

Offer Sustainability

Office Oddital lability	
Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) [™] EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	☐ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months

Product Life Status : Commercialised