Product data sheet Characteristics

NSYSBX303012

Stainless steel wall mounted industrial box, Spacial SBX, 300x300x120 mm, IP66





Main

Range	Spacial	
Product name	Spacial SBX	
Device application	Multi-purpose	
Product or component type	Industrial box	
Device short name	SBX	
Enclosure type	Flat face box	
Enclosure nominal height	300 Mm	
Enclosure nominal width	300 Mm	
Enclosure nominal depth	120 Mm	
Enclosure mounting	Wall mounted	
Device composition	4 cover screw	
	1 cover	
	1 body	
Body type	Single piece body folded and welded	
Type of front cover	Plain door	
Cover fixing	Half turn metal screw	
Lock type	Captive screw PZ2 outside sealed area	
Removable parts	Cover by captive screws	

Complementary

Material	Stainless steel 304L
Surface finish	Scotch-Brite® brushed
Standards	IEC 62208
Product certifications	BV BVM UL
IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Ambient air temperature for storage	-3560 °C
Ambient air temperature for operation	-3580 °C
Product weight	3.6 Kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	31.5 Cm
Package 1 Width	31.5 Cm
Package 1 Length	14.0 Cm
Package 1 Weight	3.324 Kg

Offer Sustainability

·		
Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	

Product Life Status : Commercialised