



Main

Range	Thalassa
Product name	Thalassa TBS
Device application	Multi-purpose
Product or component type	Industrial box
Height	291 Mm
Width	241 Mm
Depth	88 Mm
Internal height	275 Mm
Internal width	225 Mm
Internal depth	80 Mm
Enclosure mounting	Wall mounted
Device composition	1 body 1 cover 4 cover screw
Body type	One piece moulded
Type of front cover	Low transparent cover
Cover fixing	Plastic screws
Lock type	Captive screw flat outside sealed area
Removable parts	Cover by captive screws

Complementary

Material	ABS (acrylonitrile butadiene-styrene)
Colour	Grey (RAL 7035) Transparent
Standards	IEC 62208
Product certifications	TÜV
Electrical insulation class	Class II
IP degree of protection	IP66 conforming to NEMA 4.4X
IK degree of protection	IK07 conforming to IEC 62262
Fire resistance	650 °C conforming to IEC 60695-2-11
Ambient air temperature for storage	-15...40 °C
Ambient air temperature for operation	-25...60 °C
Product weight	0.92 Kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10 Cm
Package 1 Width	25 Cm
Package 1 Length	30.5 Cm
Package 1 Weight	886 G
Unit Type of Package 2	CAR
Number of Units in Package 2	8
Package 2 Height	40.5 Cm
Package 2 Width	40 Cm
Package 2 Length	60 Cm
Package 2 Weight	8.46 Kg
Unit Type of Package 3	PAM
Number of Units in Package 3	200
Package 3 Height	220 Cm
Package 3 Width	100 Cm
Package 3 Length	120 Cm
Package 3 Weight	235 Kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**