

EMG 10-OE-230AC/48DC/100/SO218 - Solid-state relay module



2311700

<https://www.phoenixcontact.com/gb/products/2311700>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Input solid-state relay, with LED and protective circuit in input and output circuits, input: 230 V AC, output: 4 - 48 V DC/max. 35 mA, customer-specific version for 50 Hz triggering

Commercial data

Item number	2311700
Packing unit	10 pc
Minimum order quantity	50 pc
Note	Made to order (non-returnable)
Sales key	CK61CY
Product key	CK61CY
GTIN	4046356287326
Weight per piece (including packing)	39.22 g
Weight per piece (excluding packing)	39.22 g
Customs tariff number	85364900
Country of origin	DE

EMG 10-OE-230AC/48DC/100/SO218 - Solid-state relay module



2311700

<https://www.phoenixcontact.com/gb/products/2311700>

Technical data

Notes

Utilization restriction

EMC note	EMC: class A product, see manufacturer's declaration in the download area
----------	---------------------------------------------------------------------------

Product properties

Product type	Solid-state relay module
Insulation characteristics	
Overvoltage category	III
Pollution degree	2

Electrical properties

Test voltage (Input/output)	3.5 kV AC (Input/output)
-----------------------------	--------------------------

Input data

Nominal input voltage U_N	230 V AC
Input voltage range in reference to U_N	0.9 ... 1.1
Input voltage range	207 V AC ... 253 V AC
Typical input current at U_N	3 mA
Operating voltage display	Yellow LED
Protective circuit	Reverse polarity protection; Polarity protection diode Surge protection
Transmission frequency	50 Hz

Output data

Design of digital output	electronic
Output nominal voltage	48 V DC
Output voltage range	4 V DC ... 48 V DC
Limiting continuous current	35 mA
Voltage drop at max. limiting continuous current	0.9 V
Output circuit	2-conductor, floating
Protective circuit	Reverse polarity protection; Polarity protection diode Surge protection

Connection data

Input side

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3

EMG 10-OE-230AC/48DC/100/SO218 - Solid-state relay module



2311700

<https://www.phoenixcontact.com/gb/products/2311700>

Conductor cross section rigid	0.2 mm ² ... 4 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12

Output side

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	0.2 mm ² ... 4 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12

Dimensions

Width	10 mm
Height	75 mm
Depth	102 mm

Material specifications

Color	green (RAL 6021)
-------	------------------

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C ... 60 °C
---------------------------------	------------------

Standards and regulations

Standards/regulations	DIN VDE 0110
	DIN VDE 0106-101

Mounting

Mounting type	DIN rail mounting
Mounting position	any

EMG 10-OE-230AC/48DC/100/SO218 - Solid-state relay module



2311700

<https://www.phoenixcontact.com/gb/products/2311700>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/gb/products/2311700>



EAC

Approval ID: RU C-DE.A*30.B.01082

EMG 10-OE-230AC/48DC/100/SO218 - Solid-state relay module



2311700

<https://www.phoenixcontact.com/gb/products/2311700>

Classifications

ECLASS

ECLASS-11.0	27371604
ECLASS-12.0	27371604
ECLASS-13.0	27371604

ETIM

ETIM 8.0	EC001504
----------	----------

UNSPSC

UNSPSC 21.0	39122300
-------------	----------

EMG 10-OE-230AC/48DC/100/SO218 - Solid-state relay module



2311700

<https://www.phoenixcontact.com/gb/products/2311700>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
	Hexahydromethylphthalic anhydride
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

EMG 10-OE-230AC/48DC/100/SO218 - Solid-state relay module



2311700

<https://www.phoenixcontact.com/gb/products/2311700>

Accessories

EMG-GKS 12 - Marking material

2947035

<https://www.phoenixcontact.com/gb/products/2947035>



Device marking label, width: 12 mm, area: 12 x 8 mm, e.g. for EML(10x7) R adhesive marking material

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk