

# DIN15W48

48V/15.36W Din Rail Power Supply



## ■ Features:

- Constant voltage design
- European AC input range
- Protections: Short circuit / Overload / Over voltage / Over temperature
- Cooling by free air convection
  - Isolation class II
- Can be installed on DIN Rail TS-35/7 or 15
  - MTBF 200.000 h

**SELV**   

## ELECTRICAL SPECIFICATION

MODEL	DIN15W48					
OUTPUT						
Rated Voltage	48V					
Rated Current	0.32A					
Current Range	0 ÷ 0.32A					
Rated Power	15.36W					
No Output Voltage (max)	52V					
Voltage Adjustment Range [6]	41-55V					
Line Regulation	± 1%					
Load Regulation	± 1%					
Tolerance [3]	± 5%					
Ripple & Noise (max.) [2]	300mV <sub>P-P</sub>					
Setup, Rise Time [4]	max 820ms, 70ms / 230VAC at full load					
Hold up Time (typ.)	65ms / 230VAC at full load					
INPUT						
Voltage Range	180 ÷ 264VAC					
Frequency Range	47 ÷ 63Hz					
Inrush current	75A at 230VAC cold start at 25°C					
Efficiency (typ.)	>81.96% - Average (25%+50%+75%+100%) /4					
AC Current (typ.)	0.35A / 230VAC					
Leakage current	<1.5mA at 50/60Hz 240VAC INPUT					
Max. No. Of PSU on Circuit Breaker	B10	B16	C10	C16	D10	D16
	22	35	22	35	45	72
No load Power Consumption (max.)	<0.5W					

# DIN15W48

48V/15.36W Din Rail Power Supply



## PROTECTIONS

<b>Over Current</b>	Range 120 ÷ 180%
	Type: hiccup mode. Recovers automatically after fault condition is removed.
<b>Short Circuit</b>	Type: hiccup mode. Recovers automatically after fault condition is removed.
<b>Over Voltage</b>	72V
	Type: hiccup mode. Recovers automatically after fault condition is removed.
<b>Over Temperature</b>	Range: NTC detect
	Type: shut down output voltage. Re-power on to recovery.

## WORKING ENVIRONMENT

<b>Working Temperature</b>	-20°C ÷ +50°C, ambient derate each output at 4.0% per degree from 50°C to 60°C
<b>Working Humidity</b>	5 ÷ 95% RH non-condensing
<b>Storage Temperature and Humidity</b>	-30°C ÷ +70°C, 5 ÷ 95% RH non-condensing

## SAFETY and EMC REGULATIONS

<b>Safety Standards</b>	Compliance to EN 62368-1
<b>Withstand Voltage</b>	IN/OUT: 3kVAC, IN/GND: 2kVAC, OUT/GND: 0.5kVAC
<b>EMC Emission</b>	Compliance to EN55032
<b>EMC Immunity</b>	Compliance to EN55035
<b>Harmonic Current</b>	Compliance to EN61000-3-3; EN61000-3-2

## OTHERS

<b>Dimensions</b>	25 x 92.5 x 56mm (L x W x H)
<b>Weight and Packing</b>	94g; 100pcs. /Box; weight box and dimensions: 10.5kg; 33.3 x 23.3 x 33.5cm

## MECHANICAL SPECIFICATION

### PIN ASSIGNMENT

NO.	Assignment
1	Input: AC/N
2	Input: AC/L
3	Output: U <sub>OUT</sub> +
4	Output: U <sub>OUT</sub> -
7	LED indication for power on
8	U <sub>OUT</sub> adjustment




# DIN15W48

48V/15.36W Din Rail Power Supply



## MECHANICAL SPECIFICATION:



1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.
2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1μF i 47μF parallel capacitor.
3. Tolerance includes set up tolerance, line regulation and load regulation.
4. Setup and rise time is measured from 0 to 90% rated output voltage.
5. Power supply is considered as component not intended to apply by end-user. Power supply meets safety and EMC standards however the final equipment with power supply must be re-qualified to comply with EMC Directives.
6. By built-in potentiometer.