

Eaton PV-350A-3L-15

Catalog Number: PV-350A-3L-15

Fuse-link, high speed, 350 A, DC 1500 V, 3L, 75 x 91 x 205 mm, gPV, UL, IEC, with indicator, blade connections

General specifications



Product Name	Catalog Number
Eaton Busmann series photovoltaic fuses	PV-350A-3L-15
	Packing Unit
	Case Pack
EAN	Quantity
5027590525824	8
Gross Weight	Length
15.68 kg	320 mm
Width	Height
280 mm	180 mm
Volume	ERP Name
16128 cm ³	SAP-UNITY
Product Length/Depth	Product Height
201.4 mm	91 mm
Product Width	Product Weight
91 mm	2600 g
Compliances	Certifications
CE Marked	IEC 60269
RoHS Compliant	UL Listed
	CSA Certified

Electrical rating

Amperage Rating

355 A

Voltage rating

1500 Vdc

Interrupt rating

100 kAIC

Class

Class gPV

Pre arc (I2T)

44000

Watt losses

84 W

Product specifications

Application

Photovoltaic systems, inverters

Fuse type

PV-3L-15

Fuse indicator

Top fuse status indicator

Fuse size

3L

Fitted with:

Blade with top indicator

Compatible fuse holder

Suitable for

SD3L-S-PV XL Fuse base

Do pobrania

Biuletyny usług serwisowych

[Datasheet - PV-350A-3L-15](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. Wszelkie
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia