Rittal – The System.

Faster – better – everywhere.

TS 4163.000
Threaded blocks

State: 27/07/2023 (Source: rittal.com/com-en)

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

TS 4163.000 - Threaded blocks

Used on enclosures and rails with rectangular system punching 12.5 x 10.5 mm with snap-off insertion aid, die-cast zinc.

Features

Model No.	TS 4163.000
Product description	With snap-off insertion aid, die-cast zinc.
Installation options	On the horizontal and vertical VX enclosure section On the vertical TS, VX SE enclosure section via adaptor rails for VX compatibility On the horizontal TS enclosure section On the horizontal VX SE enclosure section, bottom On the horizontal VX SE enclosure section, top in the depth On punched rails 23 x 23 mm On punched section without mounting flange, 23 x 73 mm On punched section without mounting flange, 45 x 88 mm On punched sections with mounting flanges, 23 x 64 mm On punched sections with mounting flanges, 23 x 73 mm On punched sections with mounting flanges, 23 x 89 mm, stainless steel On enclosures and rails with rectangular system punching 12.5 x 10.5 mm.
Dimensions	Thread: M8
To fit enclosure type	VX TS VX SE
Packs of	50 pc(s).

Features

Weight/pack	0.45 kg
Customs tariff number	79070000
EAN	4028177092969
ETIM 7.0	EC002358
ECLASS 8.0	23110815

Approvals

Approvals	GOST