

# Home - Fischerelektronik - SK 17

---

[fischerelektronik.de/web\\_fischer/en\\_GB/VA/SK17Z/datasheet.xhtml](http://fischerelektronik.de/web_fischer/en_GB/VA/SK17Z/datasheet.xhtml)

## Data sheet Product SK 17 Z

---

- [Print data sheet](#)
- [Recommend page](#)



Sockets>High-precision contacts, loose

Female contacts for Ø 0.5 mm, round contact

### Features

---

contact material: CuZn-alloy

---

contact spring: gold-plated

---

surface contact /  
contact sleeve: Ni+4...6µm Sn

---

inner contact spring material: CuBe-alloy

---

inner contact spring surface: Ni+0,75µm Au

---

plugability for circuit points:

- □0,22x0,25mm... □0,4x0,55mm
- Ø0,4...0,56mm

---

insert depth: 2.5...3.6mm

---

insertion / drawing force: 1.8 N/1.4 N

---

---

type:	female
nominal current:	1.5 A
nominal voltage:	60 V DC
test voltage:	1000 V
plug-in cross-section:	0,22x0,25mm ...0,40x0,55mm
surface of contact:	tin-plated
connection type:	THT (soldering)
grid:	2.54 mm

---

## Technical Drawing

---

