Switching probe


SKS-215 002 180 A 1502 M

Item SKS-215-0042






- For a wide range of applications: performs components detection check, is a switch for detecting closed/open states, and a signal transmitter for process control
- Various collar heights are available on the receptacles to adjust the installation height
- The installation height can be varied, and the position of the switching point can be precisely adjusted via the probe's thread. The SKS is secured in the correct position by crimp point in the KS.
- The electrical connection is ensured by installation using a receptacle, optionally available with a quick-change system for easy exchange during maintenance









3 A

General data

Product group: Switching probes Sub-product group: SKS (screwed-in) SKS-215 M plug system, screw-in Series: Grid: 2.54 mm [100 mil] Contacting from: Presence check Magnetic: Yes Installation type: Screw-in Quick-exchange system: No Type of test probe connection: Plug Adjustable installation height: Yes Non-rotating: No Screw-in torque: 3 - 5 cNm [.265 - .442 lbf·in] Compatible connector(s): SE-081 Compatible receptacle(s): KS-215 M - 40 °C [- 104 °F] Min. temperature: Max. temperature: + 80 °C [+ 176 °F] RoHS-compliant: RoHS-3;6c

Electrical data

Current load capacity / rated current:

Mechanical data

Total length: 46.5 mm [1.83 in] Barrel diameter: 1.65 mm [.064 in] Maximum stroke: 5 mm [.196 in] Spring pre-load: 0.25 N [.899 ozf] Collar height: 02 Switch path: 1.5 mm [.059 in] Switching point: 8.5 mm [.334 in] Spring force at switching point: 0.45 N [1.61 ozf]

Tip style data

Tip style: 002 flat, contact surface insulated Tip diameter: 1.8 mm [.070 in] Tip style surface: A gold Tip style material: 0 plastic

INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162 78467, Constance, Germany Phone +49 7531 8105-0 Customer hotline +49 7531 8105-888 Fax +49 7531 8105-65 info@ingun.com









Learn more about Test probes

