# Switching probe

## SKS-465 356 180 A 3502 MF

Item SKS-465-0278






- For a wide range of applications: performs components detection check, is a switch for detecting closed/open states, and a signal transmitter for process control
- Various collar heights are available on the receptacles to adjust the installation height
- The installation height can be varied, and the position of the switching point can be precisely adjusted via the probe's thread. The SKS is secured in the correct position by crimp point in the KS.
- The electrical connection is ensured by installation using a receptacle, optionally available with a quick-change system for easy exchange during maintenance







3 - 5 cNm [.265 - .442 lbf·in]

RoHS-3;6c



3 A

### **General data**

Screw-in torque:

Product group: Switching probes Sub-product group: SKS (screwed-in) Series: SKS-465 MF quick-exchange/ plug system, screw-in 3.5 mm [137 mil] Grid:

Contacting from: Pin, Post, Flat contact Magnetic: Yes Installation type: Screw-in

Quick-exchange system: Yes Type of test probe connection: Plug Adjustable installation height: Yes Non-rotating: No

Compatible connector(s): SE-215 Compatible receptacle(s): KS-465 M, KS-465 M-F Min. temperature: - 40 °C [- 104 °F]

Max. temperature: + 80 °C [+ 176 °F] RoHS-compliant:

#### **Electrical data**

Current load capacity / rated current:

#### Mechanical data

Total length: 51.3 mm [2.01 in] Barrel diameter: 2.65 mm [.104 in] Maximum stroke: 5.2 mm [.204 in] Spring pre-load: 1.02 N [3.66 ozf] Collar height: 02 Switch path: 1.7 mm [.066 in] Switching point: 15 mm [.590 in] Spring force at switching point: 1.8 N [6.47 ozf]

#### Tip style data

Tip style: 56 serrated, special length Tip diameter: 1.8 mm [.070 in] Tip style surface: A gold Tip style material: 3 CuBe

#### **INGUN** Prüfmittelbau GmbH

Max-Stromeyer-Straße 162 78467, Constance, Germany Phone +49 7531 8105-0 Customer hotline +49 7531 8105-888 Fax +49 7531 8105-65 info@ingun.com







Learn more about Test probes

