Product datasheet Characteristics

NSYS3D3420T

Spacial S3D tspt door w/o mount.plate. H300xW400xD200 IP66 IK08 RAL7035.



Price*: 88.30 GBP



Main

Main		
Range	Spacial Spacial S3D	
Product name		
Application	Multi-purpose	-
Category	Compact enclosure	
Enclosure nominal height	300 mm	
Enclosure nominal width	400 mm	
Enclosure nominal depth	200 mm	
Door type	Glazed	
Mounting plate description	Without mounting plate	
Type of gland plate	Standard	
Installation accessory type	Wall-mounting	
Device composition	Lock 1 Door 1 Body 1 Cable gland plate 1	

Complementary

Complementary			
Body type	Single piece body Gutter-shaped front rail double sheet thickness		
Number of doors	1 front face		
Door opening side	Reversible 120 °		
Lock type	3 mm double-bar lock		
Accessibility for operation	Front		
Removable parts	Door by hinges Cable gland plate by screws		
Material	Steel for body Steel and security glass for door		
Surface finish	Epoxy-polyester powder		

Colour	Grey RAL 7035		
Standards	IEC 62208		
Product certifications	GL		
	LR		
	UL		
	DNV		
	CUL		
	BV		
Product weight	5.856 kg		
Environment IP degree of protection	IP66 conforming to IEC 60529		
IK degree of protection	IK08 conforming to IEC 62262		
Offer Sustainability			
	Green Premium product		
Sustainable offer status	Green Premium product		
Sustainable offer status RoHS (date code: YYWW)	Compliant - since 0810 - Schneider Electric declaration of conformity		

REACh

Reference not containing SVHC above the threshold Available

Reference not containing SVHC above the threshold

Product environmental profile

Product Environmental Profile

Product end of life instructions

Need no specific recycling operations

Contractual warranty

Warranty period 18 months 18 months