
Product datasheet Characteristics

NSYS3D6620

Spacial S3D plain door w/o mount.plate. H600xW600xD200.IP66 IK10 RAL7035.



Price*: 98.60 GBP



Main

IVIAIII		4
Range	Spacial	
Product name	Spacial S3D	
Application	Multi-purpose	\$
Category	Compact enclosure	,
Enclosure nominal height	600 mm	
Enclosure nominal width	600 mm	
Enclosure nominal depth	200 mm	
Door type	Plain	-
Mounting plate description	Without mounting plate	!
Type of gland plate	Standard	
Installation accessory type	Wall-mounting	-
Device composition	Lock 1	
	Door 1 Body 1 Cable gland plate 1	

Complementary

Gutter-shaped front rail double sheet thickness Single piece body	
1 front face	
Reversible 120 °	
3 points lock, 3 mm double-bar	
Front	
Door by hinges Cable gland plate by screws	
Steel	
Epoxy-polyester powder	į
Grey RAL 7035	
	Single piece body 1 front face Reversible 120 ° 3 points lock, 3 mm double-bar Front Door by hinges Cable gland plate by screws Steel Epoxy-polyester powder

Standards	IEC 62208		
Product certifications	BV		
	CUL		
	DNV		
	GL		
	LR UL		
			
Product weight	14 kg		
Environment			
IP degree of protection	IP66 conforming to IEC 60529		
IK degree of protection	IK10 conforming to IEC 62262		
Offer Sustainability			
Sustainable offer status	Green Premium product		
RoHS (date code: YYWW)	Compliant - since 0810 - Schneider Electric declaration of conformity		
	Schneider Electric declaration of conformity		

Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Product environmental profile

Product end of life instructions

REACh

Warranty period 18 months 18 months

Product Environmental Profile

Need no specific recycling operations

Available