

ST/KT - EARTHING TAPES WITH PRESSED CONTACT AREAS

Construction and Application:

These connectors are manufactured from highly flexible tapes, which are braided from annealed Cu-ETP1 wires, and solderless contact areas pressed from seamless Cu-ETP tubes. The braided tapes and tubes are of same analysis and conductivity. No additives are used at the process of pressing the contact areas. Applicable as earthing tape where needed and everywhere as component for current transfer.




design D

Technical Data:

Material: 0,20 mm annealed Cu-ETP wires , uncoated (ST) or tinned (KT).

Contact Areas: Seamless Cu-ETP tube ; uncoated (ST) or tinned (KT) solderless pressed.



Catalogue No.		Cross sec.	Dim.W	Dim.L1	Dim.L	Dim.d	Amp.
Bare copper	Tinned	[mm ²]	[mm]	[mm]	[mm]	[mm]	[A]
ST-010-100-0707-D	KT-010-100-0707-D	10	14	18	100	7	75
ST-010-200-0707-D	KT-010-200-0707-D	10	14	18	200	7	75
ST-010-300-0707-D	KT-010-300-0707-D	10	14	18	300	7	75
ST-010-400-0707-D	KT-010-400-0707-D	10	14	18	400	7	75
ST-010-500-0707-D	KT-010-500-0707-D	10	14	18	500	7	75
ST-016-100-0909-D	KT-016-100-0909-D	16	16	20	100	9	120
ST-016-200-0909-D	KT-016-200-0909-D	16	16	20	200	9	120
ST-016-300-0909-D	KT-016-300-0909-D	16	16	20	300	9	120
ST-016-400-0909-D	KT-016-400-0909-D	16	16	20	400	9	120
ST-016-500-0909-D	KT-016-500-0909-D	16	16	20	500	9	120
ST-025-200-0909-D	KT-025-200-0909-D	25	20	20	200	9	135
ST-025-300-0909-D	KT-025-300-0909-D	25	20	20	300	9	135
ST-025-400-0909-D	KT-025-400-0909-D	25	20	20	400	9	135
ST-025-500-0909-D	KT-025-500-0909-D	25	20	20	500	9	135
ST-035-200-1111-D	KT-035-200-1111-D	35	25	25	200	11	195
ST-035-300-1111-D	KT-035-300-1111-D	35	25	25	300	11	195
ST-035-400-1111-D	KT-035-400-1111-D	35	25	25	400	11	195
ST-035-500-1111-D	KT-035-500-1111-D	35	25	25	500	11	195
ST-050-200-1111-D	KT-050-200-1111-D	50	30	30	200	11	250
ST-050-300-1111-D	KT-050-300-1111-D	50	30	30	300	11	250

Catalogue No.		Cross sec.	Dim.W	Dim.L1	Dim.L	Dim.d	Amp.
Bare copper	Tinned	[mm2]	[mm]	[mm]	[mm]	[mm]	[A]
ST-050-400-1111-D	KT-050-400-1111-D	50	30	30	400	11	250
ST-050-500-1111-D	KT-050-500-1111-D	50	30	30	500	11	250
ST-070-200-1313-D	KT-070-200-1313-D	70	35	35	200	13	290
ST-070-300-1313-D	KT-070-300-1313-D	70	35	35	300	13	290
ST-070-400-1313-D	KT-070-400-1313-D	70	35	35	400	13	290
ST-070-500-1313-D	KT-070-500-1313-D	70	35	35	500	13	290
ST-095-200-1717-D	KT-095-200-1717-D	95	40	40	200	17	330
ST-095-300-1717-D	KT-095-300-1717-D	95	40	40	300	17	330
ST-095-400-1717-D	KT-095-400-1717-D	95	40	40	400	17	330
ST-095-500-1717-D	KT-095-500-1717-D	95	40	40	500	17	330
ST-120-200-1717-D	KT-120-200-1717-D	120	40	40	200	17	420
ST-120-300-1717-D	KT-120-300-1717-D	120	40	40	300	17	420
ST-120-400-1717-D	KT-120-400-1717-D	120	40	40	400	17	420
ST-120-500-1717-D	KT-120-500-1717-D	120	40	40	500	17	420