





NOTE 1. () INDICATES THE REFERENCE DIMENSIONS.
2. COLORS ARE SHOWN IN TABLE-1.
3. PER PACK: 50 PIECES.

TABLE-1


PART No.	HRS No.	COLOR
TM21P-88P(11)	CL222-2862-9-11	LIGHT BEIGE
TM21P-88P(12)	CL222-2862-9-12	MEDIUM GRAY
TM21P-88P(13)	CL222-2862-9-13	BLACK
TM21P-88P(14)	CL222-2862-9-14	NATURAL LIGHT GRAY
TM21P-88P(15)	CL222-2862-9-15	RED
TM21P-88P(16)	CL222-2862-9-16	GREEN
TM21P-88P(17)	CL222-2862-9-17	BLUE
TM21P-88P(18)	CL222-2862-9-18	YELLOW
TM21P-88P(19)	CL222-2862-9-19	ORANGE
TM21P-88P(32)	CL222-2862-9-32	WHITE
TM21P-88P(33)	CL222-2862-9-33	VIOLET
TM21P-88P(34)	CL222-2862-9-34	PINK

ATTACHED HOOD CLOSED




HOOD ATTACHMENT PROCEDURE (FREE)

1. FIT THE OPENED HOOD ON THE CABLE
AND CLOSE. HOOD DIRECTION IS SHOWN
AS AN EXAMPLE.



2. SLIDE THE CLOSED HOOD TO THE PLUG
LOCK POSITION UNTIL BEING LOCKED AT
A.



NO.			1			(2) UL94V-2		
MATERIAL			POLYAMIDE			FINISH . REMARKS		
UNITS			SCALE			DESCRIPTION OF REVISIONS		
mm			2 : 1			DIS-E-001276		
HRS			APPROVED : HO. MIWA			05. 01. 05		
HIROSE			CHECKED : TH. KAMEYA			05. 01. 05		
ELECTRIC			DESIGNED : SS. SATOH			05. 01. 05		
CO., LTD.			DRAWN : SS. SATOH			05. 01. 05		
			DRAWING NO.			EDC3-121484-01		
			PART NO.			TM21P-88P (**)		
			CODE NO.					
			DESIGNED			TS. ITO		
			CHECKED			HO. MIWA		
			DATE			07. 02. 14		