

YK991	XX Number of contacts	X Cover&Flange	X Screw&Contacts plating	X Body logo	X	X	X	
	04 2*2 contacts 06 2*3 contacts 40 2*20 contacts	1 With flange & With cover 3 With flange & W/O cover	0 Screw & Contacts plating G/F 1 Screw plating Zinc & Contacts plating G/F 2 Screw plating G/F & Contacts plating Sn 3 Screw plating Zinc & Contacts plating Sn 4 Screw & Contacts plating Nickel 5 Screw steel plating zinc-nickel alloy & Contacts plating Nickel 6 Screw stainless steel & Contacts plating Nickel	0 "@" logo (standard) 1 "ANYTEK" logo	Customer's special requirements "01~99" 00 Standard	G	ROHS compliant (lead<4%) In copper alloy	H

YL	XX Number of contacts	X Pitch	X Screw&Clamp	X Color	X Body type	X	X	X	X	X
	End Stackable 04 2*2 contacts 06 2*3 contacts 48 2*24 contacts (pitch 5.0&5.08) 24 2*12 contacts (pitch 10.0&10.16)	0 5.0/.197"(left) 1 10.0/.394"(left) 2 5.0/.197"(right) 3 10.0/.394"(right) 4 5.08/0.20"(left) 5 10.16/0.40"(left) 6 5.08/0.20"(right) 7 10.16/0.40"(right)	0 "+/-" Combination type W/Brass Machined Clamp 1 "-" Slotted screw W/Brass Machined Clamp	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D)	0 Stackable 1 Solid block (only pitch 5.08-R)	0000 Standard (Steel screw plating Cr³⁺) Any special item by customer request, please contact sales department.	G	ROHS compliant (lead<4%) In copper alloy	H	ROHS compliant (lead<1000ppm) In copper alloy

YM	XX Number of contacts	X Pitch	X Screw&Clamp	X Color	X Tail length	X	X	X	X	X
	End Stackable 04 2*2 contacts 06 2*3 contacts 48 2*24 contacts (pitch 5.0&5.08) 24 2*12 contacts (pitch 10.0&10.16)	0 5.0/.197"(left) 1 10.0/.394"(left) 2 5.0/.197"(right) 3 10.0/.394"(right) 4 5.08/.20"(left) 5 10.16/.40"(left) 6 5.08/.20"(right) 7 10.16/.40"(right)	0 "+/-" Combination type W/Brass Machined Clamp 1 "-" Slotted screw W/Brass Machined Clamp	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D) C Green (RAL 6018/U)	0 3.5mm	0000 Standard (Steel screw plating Cr³⁺) Any special item by customer request, please contact sales department.	G	ROHS compliant (lead<4%) In copper alloy	H	ROHS compliant (lead<1000ppm) In copper alloy

YN	XX Number of contacts	X Pitch	X Screw&Clamp	X Color	X Tail length	X	X	X	X	X
	End Stackable 06 3*2 contacts 09 3*3 contacts 72 3*24 contacts (pitch 5.0/5.08) 36 3*12 contacts (pitch 10.0/10.16)	0 5.0/.197" 1 10.0/.394" 2 5.08/.20" 3 10.16/.40"	0 "+/-" Combination type W/Brass Machined Clamp 1 "-" Slotted screw W/Brass Machined Clamp	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D) C Green (RAL 6018/U)	0 3.5mm	0000 Standard (Steel screw plating Cr³⁺) Any special item by customer request, please contact sales department.	G	ROHS compliant (lead<4%) In copper alloy	H	ROHS compliant (lead<1000ppm) In copper alloy

YO	XX Number of contacts	X Pitch	X Screw&Clamp	X Color	X Tail length	X	X	X	X	X
	Solid Block 02 2 contacts 03 3 contacts 24 24 contacts (pitch 3.5/3.81) 12 12 contacts (pitch 7.0/7.62)	0 3.5/.138" 1 7.0/.275" 2 3.81/.15" 3 7.62/.30"	0 "+/-" Combination type W/Brass Machined Clamp 1 "-" Slotted screw W/Brass Machined Clamp	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D)	0 3.7mm	0000 Standard (Steel screw plating Cr³⁺) Any special item by customer request, please contact sales department.	G	ROHS compliant (lead<4%) In copper alloy	H	ROHS compliant (lead<1000ppm) In copper alloy